Westfield Select IP67 D-Sub Female Front Panel Mount Connectors

IP67 D-Sub Female Panel Mount - Solder Bucket Type

(Pre-made Cable Assemblies also available)


Front Panel Mount Female D-Sub

Locking via 440unc screws

Gold Flash Plating : Others Available

Straight Solder Bucket Type

We can attach custom cables if req'd





■ General information

Ambient temperature:	−25 °C ~ + 70 °C	
Connector insert:	PBT+GF	
Connector contacts:	Brass gold plated Brass nickel plated	
Coupling nut/screw:		
Seal / O-ring:	FKM	

IP rating:	IP 67 in locked condition	
Shielding:	Unavailable	
Forward resistance :	≤ 10mΩ	
Insulation resistance:	$\geq 1000 M \Omega$	

Part Numbers:

09way = IP67DSUB09FSNS

15way = IP67DSUB15FSNS

25way = IP67DSUB25FSNS

■ Electrical data & Mechanical data

Contacts Contacts	Contacts	Rated current	Voltage	
	Contacts		A/C	D/C
D-Sub 9P	Solder version	5 A	300V	300V
D-Sub 15P	Solder version	5A	300V	300V
D-Sub 25P	Solder version	5A	300V	300V

■ Remarks

For Specific Gold Plating Requirements + Mating Cycle Requirements

Please Contact Sales Office

Competitors Cross Referance Service Available

Fax: 01488 685430 sales@westfield.co.uk Tel: 01488 685183